

EUROLITE LED BAR-12 QCL RGBW Bar

LED bar (110cm) with 12 x 4 watt 4in1 QCL RGBW LED

Art. No.: 51930398

GTIN: 4026397603378



List price: 177.31 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
 - Color change adjustable; Dimmer electronic; color blend stepless
 - Strobe effect
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
 - Flicker-free
 - With a beam angle of 17°
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
 - Silent operation
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; small rental
 - Application possibility: Suspended; wall mounting
- Package contents**
- 1 x light effect, 1 x power cord, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

Logistic

EAN / GTIN: 4026397603378

Weight: 3,30 kg

Length: 1.06 m

Width: 0.14 m

Height: 0.12 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	24 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 110 cm Depth: 6,5 cm Height: 10 cm
Weight:	2,85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm ² H05RN-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm
Material:	Metal
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting