

EUROLITE LED PIX-72 RGB Bar

Bar (50 cm) with 72 wide beam RGB LEDs, 4 segments

Art. No.: 51930434

GTIN: 4026397699562



List price: 71.28 €

incl. 19% VAT.

Features:

- 72 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
4 segments controlled separately
 - Dimmer electronic; color blend stepless; color change adjustable; colors preset
 - Strobe effect
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; master/slave function; sound to light via microphone
 - Flicker-free
 - With a beam angle of 120°
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; mobile djs / entertainer
 - Silent operation
 - Application possibility: Suspended; wall mounting
- knurled screw**
- M8 thread
- Package contents**
- 1 x light effect, 1 x power cord, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

Logistic

EAN / GTIN: 4026397699562

Weight: 1,20 kg

Length: 0.55 m

Width: 0.12 m

Height: 0.11 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	IEC connector (F) mounting version
Fuse:	T 0,5 A fuse replaceable
Lamp type:	LED lamp
LED type:	72 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 6; 12
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting
Dimensions:	Length: 56,5 cm Depth: 7,0 cm Height: 9,0 cm
Weight:	1,03 kg
Noise classification:	Class 0 (no noise at all)
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm
Material:	Metal, 2 mm
Knurled screw	
Thread:	M8 thread x 16 mm
Washer	
Material:	Rubber

Dimensions:

Height: 0,3 cm

Diameter: Ø 2 cm

Legal specifications

Special product:

Not designed for household room illumination

Intended use:

Show effect lighting
