



**The article is no longer in our assortment.**

### Features:

- For application areas such as: Clubs/dancing school; wedding/gala/events; restaurants, bars and hotels
- Application possibility: Suspended
- <p>EUROLITE LED Space Tube 100 for HST Hoist
- <p class="featureSatz">Modern LED ambient light with DMX control
- Vertical and horizontal position with two hoists possible
- Particularly impressive when used in larger quantities
- 60 powerful LEDs high-power 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; Dimmer electronic; effect speed adjustable
- The device is cooled by passive convection cooling
- Control via DMX
- For application areas such as: Wedding/gala/events; clubs/dancing school; restaurants, bars and hotels

#### Package contents

- 1 x light effect
- <p>EUROLITE HST-200 Hoist
- <p class="featureSatz">Hoist for LED Space Balls 20, 35 and LED Space Tube 100
- Control via DMX
- Preprogrammed in LED PC-Control 512
- With omega bracket
- 3 digit 7-segment LED display
- Lifting height: 2 m
- For application areas such as: Clubs/dancing school; wedding/gala/events; restaurants, bars and hotels

#### Package contents

### Logistic

EAN / GTIN: 4026397699388

Weight: 8,50 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

- 1 x device, 1 x user manual

## Technical specifications:

---

Weight:	7,03 kg
Noise classification:	Class 2 (slight noise)

---

### EUROLITE LED Space Tube 100 for HST Hoist

Power supply:	24V DC
IP classification:	IP20
Protection class:	Protection class III
LED type:	60 x high-power 3in1 TCL RGB (homogenous color mix)
Cooling:	Passive convection cooling
Control:	DMX
Housing color:	White
Dimensions:	Length: 100 cm Diameter: Ø 58 cm
Weight:	0,78 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

---

### EUROLITE HST-200 Hoist

Power supply:	230 V AC, 50 Hz
Power consumption:	50 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	T 1,5 A
DMX channels:	8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	DMX
Preprogrammed in:	LED PC-Control 512
Attachment system:	Omega bracket
Display type:	3 digit 7-segment LED display
Lifting height:	2 m
Dimensions:	Width: 23,5 cm Depth: 11 cm Height: 21 cm
Weight:	6,25 kg
Noise classification:	Class 2 (slight noise)

---