eurolite®

EUROLITE Disco Strobe 25

Simple, compact strobe











List price: 16.07 €

incl. 19% VAT.

Description:

This basic strobe effect is perfectly suited for your private party room. Thanks to the mounting bracket, it can easily be mounted to a wall or ceiling. The flash frequency can be adjusted from 1-10 flashes per second using the rotary control.

Features:

- Small strobe effect with high output
- High-quality strobe flash tube
- Flash rate adjustable
- Lightweight plastic housing
- Control via stand-alone
- Strobe effect
- With a beam angle of 60°
- Very high color rendering index (CRI)
- With mounting bracket
- For application areas such as: Party room; decoration; advertisement/Shop window
- Very quiet working noise
- Application possibility: Suspended Package contents
- 1 x strobes, 1 x user manual

Technical specifications:

Power supply:

230 V AC, 50 Hz

Logistic

EAN / GTIN: 4026397617207 Weight: 0,24 kg Length: 0.17 m Width: 0.10 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power consumption:	20 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable length:	Approx. 0,9 m
Flash rate:	0 - 10 Hz
Control:	Stand-alone
Beam angle:	60°
Beam angle (1/2 peak):	60°
Color of light:	Cold white CW >5000 K
Color rendering index (CRI):	98 Ra
Attachment system:	Mounting bracket
Dimensions:	Length: 13,7 cm
	Width: 9,5 cm
	Height: 8,8 cm
Weight:	0,20 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Illuminant	
Lamp type:	Strobe lamp
Construction:	Tube
Mounting bracket	
Diameter mounting holes:	1 x Ø5mm
Material:	Plastic, 3 mm