

EUROLITE LED Super Strobe

Strobe with 480 bright SMD 5050 LEDs and DMX

Art. No.: 52200921 GTIN: 4026397656138











List price: 177.31 €

incl. 19% VAT.

Description:

With its 480 cold white SMD LEDs and the flash frequency adjustable from 1 to 20 Hz, the LED Super Strobe combines stroboscope, blinder and wash effects. It lets you create both dynamic stage shows and the more low-key effects in between with a single fixture. The very wide beam angle of 120° guarantees a great visual experience even from a lateral view. You can choose from three different operation modes: master-slave, stand-alone and DMX mode (1, 2 or 3 DMX channels). The metal housing ensures stability and is equipped with a mounting bracket, 3-pin DMX connectors and a P-Con input and output to connect the fixture to the mains.

Logistic

EAN / GTIN: 4026397656138

Weight: 4,15 kg Length: 0.45 m Width: 0.15 m Heigth: 0.30 m

Features:

- 480 powerful LEDs SMD 5050 cold white (CW)
- Strobe effect
- Control via DMX
- Flicker-free
- With mounting bracket
- Dimmer electronic; effect speed adjustable
- Preprogrammed in LED PC-Control 512; Light Captain
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; theater; mobile dis / entertainer
- Very quiet working noise
- Application possibility: Suspended

Package contents

- 1 x spotlight, 1 x power cord, 1 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

Technical specifications:

<u> </u>	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
Lamp type:	LED lamp
LED type:	480 x SMD 5050 cold white (CW)
Flash rate:	1 - 20 Hz
DMX channels:	1; 2; 3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	120°
Color temperature:	6500K
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 46 cm
	Depth: 8 cm
	Height: 25,5 cm
Weight:	3,75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Power cord	
Cable construction:	3 x 1 mm² H05VV-F
Cable length:	Approx. 1,5 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 2 x Ø8mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting