# eurolite®

### **EUROLITE Techno Strobe 250**

Compact strobe with 40 W flash tube and adjustable flash frequency

Art. No.: 52201070 GTIN: 4026397614169



## List price: 35.58 €

incl. 19% VAT.

#### **Description:**

This basic strobe effect with a 40-watt flash tube is perfectly suited for your private party room. Thanks to the mounting bracket, it can easily be mounted to a wall or ceiling. The flash frequency can be adjusted from 1-10 flashes per second using the rotary control.

#### Features:

- High-quality reflector
- Flash frequency steplessly adjustable
- Flash tube already installed
- Compact design
- Strobe effect
- Control via stand-alone
- Very high color rendering index (CRI)
- For application areas such as: Party room; advertisement/Shop window
- Very quiet working noise
- Application possibility: Suspended Package contents
- 1 x device, 1 x user manual

#### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	45 W

#### Logistic

EAN / GTIN: 4026397614169 Weight: 0,53 kg Length: 0.20 m Width: 0.14 m Heigth: 0.17 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable construction:	2 x 0,75 mm² H03VVH2-F
Cable length:	Approx. 0,8 m
Lamp type:	Strobe lamp
Flash rate:	1 - 10 Hz
Color generation:	Cold white (CW)
Control:	Stand-alone
Color rendering index (CRI):	98 Ra
Dimensions:	Length: 16,5 cm
	Width: 17,5 cm
	Height: 17 cm
Weight:	0,42 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Mounting bracket	
Diameter mounting holes:	1 x Ø9mm
Material:	Plastic, 2,5 mm