

# **EUROLITE AKKU LED Party Tube IR**

Battery operated LED color tube with IR remote control

Art. No.: 52500216 GTIN: 4026397713275



List price: 83.18 €

incl. 19% VAT.

## Features:

- Extraordinary lighting for an enchanting atmosphere
- The milky PVC housing provides for a lovely appearance as well as for atmospheric illumination
- Incl. 3 easy-to-connect parts as stand for upright mounting and clips for wall or ceiling mounting
- Battery operation up to 8h
- 32 powerful LEDs SMD 5050 3in1 TCL RGB
- Program speed adjustable; Dimmer electronic
- Strobe effect
- 10 integrated show programs
- Direct color selection for 12 preset colors
- Control via on/off switch on device; IR remote control
- With a beam angle of 300°
- Cordless, flexible and versatile
- For application areas such as: Wedding/gala/events; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; wall mounting

## Package contents

 1 x device, 1 x user manual, 1 x external mains adapter, 1 x remote control, 2 x mounting bracket, 3 x stand, 1 x battery

#### **Technical specifications:**

Power supply:	12,6V DC
IP classification:	IP20

#### Logistic

EAN / GTIN: 4026397713275

Weight: 0,72 kg Length: 1.12 m Width: 0.08 m Heigth: 0.06 m

Battery pack type:  1 x lithium ion 11,1 V, 2500 mAh, 27,7 Wh  Battery pack:  Battery operation up to 8h Recharging time 4h	ection class:	Protection class III
Battery pack:  Battery operation up to 8h Recharging time 4h  Battery:  1 x button cell 3.0 V CR2025 lithium mangabuilt-in  Lamp type:  LED lamp  LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  300° multicolor  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm Height: 100 cm	er connection:	Mains input via coaxial power connector (M) power supply cord with AC adapter (provided)
Recharging time 4h  Battery:  1 x button cell 3.0 V CR2025 lithium mangabuilt-in  Lamp type:  LED lamp  LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  300° multicolor  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm	ry pack type:	1 x lithium ion 11,1 V, 2500 mAh, 27,7 Wh
built-in  Lamp type:  LED lamp  LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm	ry pack:	
LED type:  32 x SMD 5050 3in1 TCL RGB  Flash rate:  0 - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  4 300° multicolor  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm	ry:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Flash rate:  O - 30 Hz  Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm	type:	LED lamp
Control:  On/off switch on device; IR remote control  Beam angle:  300°  Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm	type:	32 x SMD 5050 3in1 TCL RGB
Beam angle: 300°  Beam angle (1/2 peak): 300° multicolor  Housing color: White; semi-transparent  Dimensions: Width: 20 cm Height: 100 cm	rate:	0 - 30 Hz
Beam angle (1/2 peak):  Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm Height: 100 cm	rol:	On/off switch on device; IR remote control
Housing color:  White; semi-transparent  Dimensions:  Width: 20 cm  Height: 100 cm	n angle:	300°
Dimensions: Width: 20 cm Height: 100 cm	n angle (1/2 peak):	300° multicolor
Height: 100 cm	sing color:	White; semi-transparent
	nsions:	Height: 100 cm
Weight: 0,56 kg	ht:	0,56 kg
Noise classification: Class 0 (no noise at all)	e classification:	Class 0 (no noise at all)