



List price: 11.78 €

incl. 19% VAT.

Features:

- Rope with thimble and connector
- <p>EUROLITE Steel Rope 1000x6mm silver with Thimble
- <p class="featureSatz">Installation rope, safety bond, safety
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble
- For further information about this product, please refer to the Data Sheet under "Downloads"
- <p>EUROLITE Quick Link Type B-200
- <p class="featureSatz">Quick link
- Complies with DIN 56927:2009-03

Logistic

Technical specifications:

Secured weight (BGV C1):	Max. 35 kg
Temperature range:	-40° C - +100° C
Weight:	0,22 kg

EUROLITE Steel Rope 1000x6mm silver with Thimble

Maximum load WLL (5-fold):	400 kg
Design of the core:	6 x 19 FC
Strength classification:	1960
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strength of rope:	1770 N/mm ²
Wire surface:	Zinc-plated
Color:	Silver
Temperature range:	-40° C - +100° C
Dimensions:	Length: 100 cm Diameter: Ø 0,60 cm
Weight:	0,19 kg
Length weight:	0,0554 kg/m

EUROLITE Quick Link Type B-200

Maximum load WLL (10-fold):	200 kg
Standard:	DIN 56927:2009-03,
Shape:	B - big opening
Material:	Steel, zinc-plated
Opening:	0-14,5 mm
Dimensions:	Length: 5,80 cm Width: 7,30 cm Depth: 3 cm Diameter: Ø 0,60 cm
Weight:	0,03 kg