

EUROLITE Safety Bond A 3x600mm up to 5kg, black

Approved safety bond

Art. No.: 58010341

GTIN:



List price: 6.55 €

incl. 19% VAT.

Features:

Approved safety bond

- Rope with thimble and connector

EUROLITE Steel Rope (SC) 600x3mm black with thimbles

Installation rope, safety bond, safety

- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble

EUROLITE Quick Link Typ A-50 black

Quick link

- Complies with DIN 56927:2009-03

Package contents

- 1 x device

Technical specifications:

Logistic

Secured weight (BGV C1):	Max. 5 kg
Strength classification:	1770
Temperature range:	-40° C - +100° C
Weight:	0,05 kg

EUROLITE Steel Rope (SC) 600x3mm black with thimbles

Maximum load WLL (5-fold):	100 kg
Design of the core:	6 x 19 WSC
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strength of rope:	1770 N/mm ²
Wire surface:	Zinc-plated
Color:	Black
Temperature range:	-40° C - +100° C
Dimensions:	Length: 60 cm Diameter: Ø 0,30 cm
Weight:	0,04 kg
Length weight:	0,0311 kg/m

EUROLITE Quick Link Typ A-50 black

Maximum load WLL (10-fold):	50 kg
Standard:	DIN 56927:2009-03,
Shape:	A - small opening
Material:	Steel, zinc-plated
Opening:	0-5,5 mm
Dimensions:	Length: 2,90 cm Width: 3,50 cm Depth: 1,90 cm Diameter: Ø 0,30 cm
Weight:	0,01 kg