alutruss

ALUTRUSS U-Frame Base Part

Single tube with QUICK-LOCK

Art. No.: 60320350 GTIN: 4026397594874





List price: 189.21 €

incl. 19% VAT.

Features:

- The number of U-frames that can be used is the sum of the net weights of the U-frames plus any added loads and must not exceed the carrying capacity of the U-frame top section (60320351)
- Each frame must be connected at two points to the frame above it with the enclosed connectors
- A frame must be secured by the two eyelets welded to the side tubes
- The drop distance should be less than 10 cm
- Use sufficiently sized steel cables or chains as securing means
- Load capacity of a U-frame: point load 100 kg
- Strong EN-AW 6082 alloy for high loads
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Stage; clubs/dancing school; rental

Technical specifications:

Trusspipe:	50 mm
Color:	Alu colored
Dimensions:	Length: 60 cm
	Width: 5 cm
	Height: 55 cm
Weight:	2,45 kg

Logistic

EAN / GTIN: 4026397594874 Weight: 2,65 kg Length: 0.60 m Width: 0.06 m Heigth: 0.56 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.