alutruss

ALUTRUSS Gizmo/Clamps Truss Adapter black

Truss mount

Art. No.: 60320385 GTIN: 4026397570458







List price: 141.61 €

incl. 19% VAT.

Features:

Truss mount

- With two TPC-50 clamps
- Trusspipe: 50 mm

ALUTRUSS GI-1 Truss Adapter black

Truss mount

- U-profile for hanging truss from the ceiling
- Designed for trusses from 25 to 40 cm
- Thanks to its adjustable system, just one adapter can be used for different trusses
- M20 ring bolt with washer and self-locking nut
- LGA tested

EUROLITE TPC-50S Half Coupler

Mounting coupler for 50 mm tube, maximum load WLL 800 kgPackage contents

- 1 x device, 1 x user manual

Technical specifications:

Logistic

EAN / GTIN: 4026397570458 Weight: 3,90 kg Length: 0.41 m Width: 0.31 m Heigth: 0.28 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Trusspipe:	50 mm
Weight:	3,87 kg

ALUTRUSS GI-1 Truss Adapter black

Maximum load BGV C1 (8-fold):	250 kg
Maximum load WLL (4-fold):	500 kg
Color:	Black
Material thickness:	3,5 mm
Dimensions:	Length: 40 cm Width: 8 cm
	Height: 5 cm
Weight:	2,46 kg

EUROLITE TPC-50S Half Coupler

Maximum load BGV C1 (8-fold):	400 kg
Maximum load WLL (4-fold):	800 kg
Tube diameter sector:	45 - 50 mm
Material:	Aluminum
Color:	Black
Mounting screw:	M10
Dimensions:	Length: 11 cm Width: 5 cm
	Depth: 11,50 cm
Weight:	0,71 kg