## **EUROLITE DPX-620 DMX Dimmer Pack**

Digital 6-channel dimmer pack

eurolite









# List price: 593.81 €

incl. 19% VAT.

### Features:

- Universal dimmer pack for professional use
- Can be operated 1-phase or 3-phase
- DMX control or analog control possible
- The DMX-starting address can be adjusted on the device
- Synchronization of several devices possible via DMX
- Adjusting the lamp pre-heat
- With automatic circuit breaker per channel
- Channel-outputs on the rearpanel via pole connectors
- Only for professional use
- Preprogrammed 12 scenes/chases
- Control via analog 0-10 V; stand-alone; DMX
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Trade fair and shop fitting; stage; theater; rental
- Very quiet working noise Package contents
- 1 x device, 1 x user manual

#### **Technical specifications:**

Power supply:	230/380 V AC, 50 Hz
Output power:	Max. 4600 W per channal
	Max. 27600 W
Output current:	Max. 120 A

#### Logistic

EAN / GTIN: 4026397229776 Weight: 9,10 kg Length: 0.53 m Width: 0.49 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via screw terminal
Power output:	Screw terminal
Power output fuse per channel:	C 20 A fuse resettable
Programs:	Preprogrammed 12 scenes/chases
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	Analog 0-10 V; stand-alone; DMX
Control channels:	6
Color:	Black
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm
	Depth: 42 cm
	Height: 8,9 cm
Weight:	7,70 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)