

## EUROLITE DPMX-1216 DMX Dimmer Pack

12 x 16A dimmer, service friendly modules, connection via terminal block

Art. No.: 70064180

GTIN: 4026397521757



**List price: 1188.81 €**

incl. 19% VAT.

### Description:

Reliability is always important. Especially at professional events the breakdown of any part of the equipment cannot be accepted. The DPMX-1216 dimmer pack series is the right answer here because it plays it safe: this universal output stage has an automatic circuit breaker on every channel, so single failures can be corrected without causing a complete blackout. Another benefit are the different outputs. Pole connector, safety plug, CEE or multipin: the DPMX-1216 19" serves really any kind.

### Logistic

EAN / GTIN: 4026397521757

Weight: 20,20 kg

Length: 0.63 m

Width: 0.56 m

Height: 0.28 m

### Features:

- 12-channel dimmer pack with up to 16 A output per channel
- Modular design of the individual dimmer modules for quick and easy change
- 3-phase or 1-phase power supply
- Adjustable lamp preheat (0-50%) and limiter function to prolong bulb life
- Curve function for selection of different fade modes
- Dim or switch option assignable to each channel
- DMX Fail function: automatic digital input check to detect DMX signal errors
- Manual mode for dimming capability without an external lighting controller
- Synchronization of several devices possible via DMX
- Automatic circuit breaker per channel (type C)
- Channel-outputs on the rearpanel via pole connectors
- Only for professional use
- 12 integrated show programs
- Preprogrammed 12 scenes/chases
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- LCD display

- (19") 48.3 cm rack installation 4 U
- For application areas such as: Trade fair and shop fitting; stage; theater; rental
- Very quiet working noise

**Package contents**

- 1 x device, 1 x user manual

**Technical specifications:**

|                                |  |
|--------------------------------|--|
| Power supply:                  | 230/380 V AC, 50 Hz  |
| Protection class:              | Protection class I   |
| Output power:                  | Max. 43470 W<br>Max. 3680 W per channel                                  |
| Output current:                | Max. 189 A   |
| Power connection:              | Mains input via screw terminal   |
| Power output:                  | Screw terminal   |
| Power output fuse per channel: | C 16 A fuse resettable   |
| Programs:                      | Preprogrammed 12 scenes/chases   |
| DMX channels:                  | 12   |
| DMX input:                     | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version |
| DMX output:                    | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version |
| Cooling:                       | Cooling fan  |
| Control:                       | Stand-alone; DMX   |
| Control channels:              | 12   |
| Display type:                  | LCD display  |
| Color:                         | Black  |
| Housing design:                | (19") 48.3 cm rack installation 4 U                                      |
| Dimensions:                    | Width: 48,3 cm<br>Depth: 48,5 cm<br>Height: 17,8 cm                      |
| Weight:                        | 18,20 kg   |
| Noise classification:          | Class 1 (very slight noise, suitable for noise-sensitive environments)   |