

MADRIX LUNA 8 Port USB / Art-Net Node

Art-Net and USB interface for output of 4096 channels

Art. No.: 70064845 GTIN: 4260263421080



List price: on demand €

incl. 19% VAT.

Features:

- Can receive and process up to 512 DMX channels
- Can transmit up to 4096 DMX channels
- The device is cooled by passive convection cooling
- Control via Art-Net
- Built with NEUTRIK connector
- The device can be connected via USB to the PC
- (19") 48.3 cm rack installation 1 U
- Made in Germany
- The device can be connected via RJ-45 etherCON (F) mounting version to the PC
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	5 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
DMX channels:	Input 512 Output 4096

Logistic

EAN / GTIN: 4260263421080

Weight: 2,10 kg Length: 0.53 m Width: 0.17 m Heigth: 0.07 m

DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	8 x 5-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 1x RJ-45 etherCON (F) mounting version
Cooling:	Passive convection cooling
Control:	Art-Net
USB port:	USB 2.0, type B
Use of brands:	Built with NEUTRIK connector
PC connect:	Via USB Via RJ-45 etherCON (F) mounting version
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm
	Depth: 7,6 cm
	Height: 4,45 cm
Weight:	1,65 kg