

## EUROLITE DXT-SP 1in/8out PRO DMX RDM Splitter 5pol XLR

RDM-capable DMX splitter, 1in/8out with signal boost

Art. No.: 70064870

GTIN: 4026397572506



**The article is no longer in our assortment.**

### Features:

- DMX splitter for splitting one DMX input signal to 8 DMX outputs
- Input and feed-through output are duplicated on the front and rear panel and connected in parallel
- Switchable filter mode allows all RDM data to be filtered out in order to prevent problems when using fixtures intolerant of RDM
- Bypass function to process signals from older devices similar to DMX signals
- Output frequency adjustable: 22/44 Hz
- Switchable termination resistor
- Outputs galvanically isolated
- Each DMX output can be connected to 32 DMX devices
- Control via RDM
- DMX feed-through for up to 32 further DMX devices<BR>RDM For bidirectional communication over the DMX line<BR>RDM switchable to prevent problems when using fixtures without RDM
- Built with NEUTRIK connector
- (19") 48.3 cm rack installation 1 U
- Made in Germany
- Each DMX output with active signal processing

### Package contents

- 1 x device, 1 x external mains adapter, 4 x foot, 1 x user manual

### Logistic

EAN / GTIN: 4026397572506

Weight: 2,20 kg

Length: 0.55 m

Width: 0.26 m

Height: 0.06 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz  
12V DC 1000 mA

Power consumption:	6 W
Power connection:	Power supply cord with AC adapter (provided)
DMX input:	2 x 5-pin XLR (M) mounting version
DMX output:	2 x 5-pin XLR (F) mounting version Bypass 8 x 5-pin XLR (F) mounting version separate (galvanic) with active signal processing
Control:	RDM
DMX features:	DMX feed-through for up to 32 further DMX devices  RDM For bidirectional communication over the DMX line  RDM switchable to prevent problems when using fixtures without RDM
Use of brands:	Built with NEUTRIK connector
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm Depth: 10 cm Height: 4,43 cm
Weight:	1,92 kg