eurolite®

EUROLITE AF-180 Stage Fan DMX

High-performance DMX wind machine with adjustable air discharge angle

Art. No.: 80208075 GTIN: 4026397719154











List price: 593.81 €

incl. 19% VAT.

Features:

- Great effect when used e.g. with fog, snow and bubble machines
- Output volume adjustable
- Air discharge angle adjustable
- Quick truss installation via QUICK-LOCK Omega bracket
- Rugged metal housing
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Monochrome LCD display
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; theater; video and photography
- Application possibility: Standing; suspended

```
Package contents
```

- 1 x device, 1 x user manual, 1 x power cord, 2 x omega bracket

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	180 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug

Logistic

EAN / GTIN: 4026397719154 Weight: 13,50 kg Length: 0.52 m Width: 0.44 m Heigth: 0.43 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Speed: 880 RPM - 2650 RPM Maximum airflow: 3300 m³/h DMX channels: 1 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Control: Stand-alone; DMX; QuickDMX via USB (optional); CRMX by vireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Housing color: Black Display type: Monochrome LCD display USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg Noise classification: Class 3 (clearly perceptible sounds)	Power output:	1 x P-Con (gray), mounting version
DMX channels: 1 DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version DMX output: 1 x 5-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Control: Stand-alone; DMX; QuickDMX via USB (optional) W-DMX by wireless solution via USB (optional) Housing color: Black Display type: Monochrome LCD display USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg	Speed:	880 RPM - 2650 RPM
DMX input: 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Control: Stand-alone; DMX; QuickDMX via USB (optional) W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Housing color: Black Display type: Monochrome LCD display USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg	Maximum airflow:	3300 m³/h
1 x 5-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Control: Stand-alone; DMX; QuickDMX via USB (optional) W-DMX by wireless solution via USB (optional) Housing color: Black Display type: Monochrome LCD display USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg	DMX channels:	1
DMX output: 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version Control: Stand-alone; DMX; QuickDMX via USB (optional) W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Housing color: Black Display type: Monochrome LCD display USB port: Type A Carrying handle: Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight:	DMX input:	1 x 3-pin XLR (M) mounting version
1 x 5-pin XLR (F) mounting version Control: Stand-alone; DMX; QuickDMX via USB (optional) W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Housing color: Black Display type: Monochrome LCD display USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg		1 x 5-pin XLR (M) mounting version
Control: Stand-alone; DMX; QuickDMX via USB (optional) W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Housing color: Black Display type: Monochrome LCD display USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg	DMX output:	1 x 3-pin XLR (F) mounting version
W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) Housing color: Black Display type: Monochrome LCD display USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg		1 x 5-pin XLR (F) mounting version
Display type: Monochrome LCD display USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg	Control:	, , , , , , , , , , , , , , , , , , , ,
USB port: Type A Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg	Housing color:	Black
Carrying handle: 1 pc/pcs Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg	Display type:	Monochrome LCD display
Dimensions: Length: 44 cm Width: 25 cm Height: 48,5 cm Weight: 11,65 kg	USB port:	Туре А
Weight: 11,65 kg	Carrying handle:	1 pc/pcs
Height: 48,5 cm Weight: 11,65 kg	Dimensions:	Length: 44 cm
Weight: 11,65 kg		Width: 25 cm
		Height: 48,5 cm
Noise classification: Class 3 (clearly perceptible sounds)	Weight:	11,65 kg
	Noise classification:	Class 3 (clearly perceptible sounds)