


EUROLITE LSD-20 MK2 (H)2.56m x (W)1.28m

LED soft displays

Art. No.: 80503260

GTIN: 4026397459814



List price: 8384.49 €

incl. 19% VAT.

Features:

- Flexible displays with tricolor RGB LEDs (type SMD 5050) for bright and colorful projection of videos and graphics
- Improved version with even brighter LEDs and new angled connectors
- Modular display concept allows the build-up of large areas, ideal for outdoor use with large viewing distances
- Bendable and foldable PVC material suitable for various shapes, e.g. columns, circles, angles
- Truss suspension via built-in belts
- Easy maintenance - LEDs can be replaced without difficulty
- Controllable via optional network components and PC software
- All-in-one control system T9 (80503301): network interface and software LED Show T9 - ideal system for mobile use with notebooks with 1-gigabit NIC
- Control system LED studio: receiver interface (80503311), PCI sending card and software LED Studio (80503130)
- Custom sizes available upon request (in 0.32 m units)
- 8192 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Easy to assemble
- Various versions available
- B1 low flammability
- Space-saving construction
- Space-saving storing
- Water repellent
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397459814

Weight: 34,45 kg

Length: 1.32 m

Width: 0.68 m

Height: 0.19 m

Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	68,00 W
IP classification:	IP44
LED type:	8192 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Setup:	Easy to assemble; Space-saving construction; space-saving storing
Beam angle (1/2 peak):	110°
Image:	Max. 64x124 px Pixel pitch 20 mm Pixel density 2500/m ² Brightness 3600cd/m ²
Lamp life:	100000 h
Material:	, water repellent
Dimensions:	Width: 128 cm Height: 256 cm
Weight:	31,72 kg
Display port:	DVI/RJ45
Display mode:	synchronous to video source
Drive mode:	1/8 scan
Screen resolution:	max. 1280 x 1024 (LED Studio) max. 1024 x 896 (LED Show T9)
Frame rate:	60 Hz
Data refresh rate:	600 Hz
Colors:	16.7 million (R 256, G 256, B 256)
Operating temperature:	-10 to 45 °C
Humidity:	10 to 90 %