

OMNITRONIC MP-60P PA Mixing Amplifier

PA mixing amplifier with audio player, IR remote control, 60 W RMS

Art. No.: 80709611 GTIN: 4026397503449







List price: 320.11 €

incl. 19% VAT.

Features:

- SD card slot and USB port

- Folder navigation and repeat functions (1, All)
- 3 microphone inputs (6.3 mm jack, unbal.) with separate level controls
- Microphone input 3 with adjustable priority circuit
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-digit LED level meter
- Master control for the output signal
- The device is cooled by cooling fan
- Control via IR remote control
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- LCD display
- Package contents
- 1 x amplifier, 1 x remote control, 1 x battery, 1 x user manual

Technical specifications:

| Power supply: | 230 V AC, 50 Hz |
|--------------------|--------------------|
| Power consumption: | 120,00 W |
| Protection class: | Protection class I |

Logistic

EAN / GTIN: 4026397503449 Weight: 8,70 kg Length: 0.54 m Width: 0.49 m Heigth: 0.18 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Output power: | 60 W RMS |
|--------------------------|---|
| Power connection: | Fixed power supply cord with safety plug |
| Device fuse: | 5 x 20 mm, T 1 A fuse replaceable |
| Frequency range: | 80 - 14000 Hz |
| S/N ratio: | >75 dB microphone >85 dB line |
| THD: | <0,5 % at 1 kHz |
| Cooling: | Cooling fan |
| Impedance: | Public address systems 100V; 4-16 ohms; Public address systems 70V |
| Control: | IR remote control |
| Audio player: | USB + SD |
| Circuitry: | Class AB |
| Display type: | LCD display |
| Controls: | Power on/off transient; Overvoltage; short-circuit |
| Status LED: | Power, fault, level meter |
| Connections: | Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 3 x stereo RCA 0,3 V Output: line via 1 x stereo RCA 0,3 V |
| Equalizer: | Output: speaker via screw terminal Master: 1 x 2-band tone control mono |
| Music format: | MP3 |
| Number of files: | Max. 999 |
| Available storage media: | USB devices/SD cards max. 32GB (FAT 32) |
| Housing design: | (19") 48.3 cm rack installation 2 U |
| Dimensions: | Width: 48,3 cm |
| | Depth: 40 cm Height: 8,9 cm |
| Weight: | 7,25 kg |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |