

## OMNITRONIC CPZ-120P PA Mixing Amplifier

Art. No.: 80709704

4-zone-PA mixing amplifier with audio player, IR remote control and Bluetooth, switchable zones, 120 W RMS

GTIN: 4026397683219



List price: 343.91 €

incl. 19% VAT.

### Features:

- 4 PA zone outputs, independently switchable on the front panel
  - Output for low-impedance speakers (4-16 ohms)
  - SD card slot and USB port
  - FM tuner with auto scan
  - 3 microphone inputs with separate level controls
  - Mic 1 with phantom power, priority circuit and echo effect
  - Mic 2 and 3 switchable mic/line
  - 2 line inputs with separate level controls
  - 1 line output
  - Siren and chime, adjustable
  - Treble and bass and master controls for the output signal
  - 5-digit LED level meter
  - Mains operation and 24 V emergency power operation
  - The device is cooled by cooling fan
  - Control via Bluetooth; IR remote control
  - 2 U
  - Desktop console housing
  - For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- Package contents**
- 1 x amplifier, 1 x remote control, 1 x antenna, 1 x battery, 1 x power cord, 1 x user manual, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397683219  
Weight: 4,10 kg  
Length: 0.35 m  
Width: 0.27 m  
Height: 0.14 m

## Technical specifications:

---

Power supply:	100-240 V AC, 50/60 Hz Or 24V
Power consumption:	240 W
Protection class:	Protection class I
Output power:	120 W RMS
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  Battery/battery pack (not included)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Cooling:	Cooling fan
Impedance:	Public address systems 70V; public address systems 100V; 4-16 ohms
Control:	Bluetooth; IR remote control
Bluetooth device name:	OMNITRONIC
Audio player:	USB + SD + Bluetooth + FM radio
Zone output:	4 switchable zones
Circuitry:	Class D
Control elements:	Power switch
Controls:	Overload; short-circuit; limiter; overheat
Connections:	Input: microphone via 1 x 3-pin XLR Input: mic/line via 2 x 6.3 mm jack socket (stereo) mounting version Input: line via 2 x stereo RCA Output: line via 1 x stereo RCA 0,774 V Output: speaker via screw terminal
Equalizer:	Master: 1 x 2-band tone control
Music format:	MP3
Housing design:	2 U Desktop console housing
Dimensions:	Width: 30,3 cm Depth: 22 cm Height: 9,1 cm
Weight:	3,85 kg