

## OMNITRONIC MAVZ-120.6P PA Mixing Amplifier

6-zone-PA mixing amplifier with audio player and remote control, adjustable zones, 120 W RMS

Art. No.: 80709788

GTIN: 4026397703627



**List price: 415.31 €**

incl. 19% VAT.

### Features:

- Comfortable control of PA speakers via 6-zone technology
  - 6 PA zone outputs with separate 5-step level controls
  - Output for low-impedance speakers (4-16 ohms)
  - SD card slot and USB port
  - Folder navigation, repeat functions and random play
  - 3 microphone inputs with separate level controls
  - Mic 1 with phantom power and priority circuit
  - Mic 2 and 3 switchable mic/line
  - 2 line inputs with separate level controls
  - 1 line output
  - Treble and bass and master controls for the output signal
  - 5-digit LED level meter
  - Chime, switchable
  - The device is cooled by cooling fan
  - Control via IR remote control; Bluetooth
  - LCD display
  - (19") 48.3 cm rack installation 2 U
  - For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- Package contents**
- 1 x amplifier, 1 x remote control, 1 x battery, 2 x holder, 4 x screw, 1 x user manual

### Logistic

EAN / GTIN: 4026397703627

Weight: 7,10 kg

Length: 0.53 m

Width: 0.44 m

Height: 0.18 m

### Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption:	240 W
Protection class:	Protection class I
Output power:	120 W RMS
Power connection:	Fixed power supply cord with safety plug
Device fuse:	5 x 20 mm, T 3 A fuse replaceable
Frequency range:	50 - 18000 Hz
S/N ratio:	>75 dB microphone >85 dB line
THD:	<0,5 % at 1 kHz
Cooling:	Cooling fan
Impedance:	Public address systems 100V; 4-16 ohms; Public address systems 70V
Control:	IR remote control; Bluetooth
Audio player:	USB + SD + Bluetooth
Housing color:	Black
Zone output:	6 adjustable zones
Circuitry:	Class AB
Display type:	LCD display
Control elements:	Power switch, Master control, level control per channel, tone control, audio player
Controls:	Current limiting; short-circuit; power on/off transient; power on/off transient; Overvoltage; short-circuit
Status LED:	Power, fault, level meter
Connections:	Input: microphone via 1 x 3-pin XLR Input: microphone via 2 x 6.3 mm plug (unbal.) Input: line via 2 x stereo RCA 0,3 V Output: line via 1 x stereo RCA Output: speaker via screw terminal
Equalizer:	Master: 1 x 2-band tone control mono
Music format:	MP3
Number of files:	Max. 999
Available storage media:	USB devices/SD cards max. 32GB (FAT 32)
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 32 cm Height: 9,2 cm
Weight:	5,70 kg
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in