

OMNITRONIC PS-25 Projector Speaker

Bidirectional speaker (2 x 5") with mount











incl. 19% VAT.

Features:

- 2 built-in speakers for bidirectional radiation
- Durable aluminum cabinet with grille
- With mounting bracket
- Suitable for outdoor use IP44
- For application areas such as: Installation
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x device, 1 x user manual, 1 x lid

Logistic

EAN / GTIN: 4026397279566 Weight: 3,20 kg Length: 0.18 m Width: 0.18 m Heigth: 0.28 m

Technical specifications:

IP classification:	IP44
Power connection:	Fixed supply cord with open wires
Power:	Program: 20W
	Rated: 10W RMS
Frequency range:	130 - 15000 Hz
Sensitivity:	91 dB (1W/1m)
Max. SPL:	101 dB
Impedance:	Public address systems 100V
Attachment system:	Mounting bracket

Power tapping:	2,5W; 5W; 10W RMS via no connector/cable only switchable
Speaker:	2 x woofer 5"
Type of speaker:	Projector speaker
Material:	Aluminum
Color:	White
Dimensions:	Depth: 20,5 cm Diameter: Ø 13,8 cm
Weight:	2,9 kg