

OMNITRONIC WP-4S PA Wall Speaker

2-way speaker with mount, public address systems 100V, 20 W RMS

Art. No.: 80710510

GTIN: 4026397412086





List price: 65.33 €

incl. 19% VAT.

Features:

- 2-way system
- Trapezoidal cabinet for corner installation
- With mounting bracket
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x device, 1 x user manual

Technical specifications:

Power connection:	Fixed supply cord with open wires
Power:	Program: 40W Rated: 20W RMS
Frequency range:	90 - 20000 Hz
Sensitivity:	89 dB
Max. SPL:	101 dB
Impedance:	Public address systems 100V
Attachment system:	2x M6 thread 1x mounting bracket
Speaker:	1 x woofer 4"

Logistic

EAN / GTIN: 4026397412086 Weight: 2,55 kg Length: 0.23 m Width: 0.21 m Heigth: 0.27 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	PP polypropylene
	1 x tweeter 1"
	PP polypropylene with wave guide
Type of speaker:	Compact cabinet speaker
Type of construction:	Closed Box
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black, scratchproof and shockproof
Dimensions:	Width: 17 cm
	Depth: 15 cm
	Height: 21,5 cm
Weight:	2,10 kg