

LASERWORLD EL-230RGB MK2

Laser de spectacle de classe 3B, 230 mW en rouge, vert et bleu

Réf. : 51743209

GTIN: 7640144991630



Prix de catalogue: 184.45 €

TVA 19% incl.

Description:

The Laserworld EL-230RGB MK2 is a RGB laser system with a total output power of up to 230 mW.

The red diode laser module with a wavelength of 650 nm, the green DPSS laser module with a wavelength of 532nm and the royal-blue laser module with a wavelength of 445 nm ensure beautiful colors and brightness. The beams have a diameter of about ca. 4 mm and a beam divergence of about 1 mrad and the projector offers high-speed step motors, up to 2-5 kpps as well as a scan angle of up to 30°. About ca. 50 (layers, tunnels, fences, waves, etc.) can be controlled via DMX. A sound-to-light mode as well as a stand-alone mode are available too. For the sound-to-light mode the sensitivity of the integrated adjustable microphone can be adjusted.

There is an interlock connector for safety switch as well as a key switch at the rear side of this very compact device.

The Laserworld EL-230RGB MK2 is a good solution for first-time users and mobile use and it is often used in bars, small clubs, at private parties or for home use.

With ultra bright 445 nm royal blue!

Caractéristiques:

- Commandé via DMX; stand-alone; commande de la musique via microphone
- Avec étrier
- Pour des domaines d'application tels que: Cave aménagée pour les fêtes; DJ itinérants / artistes solos; clubs/écoles de danse
- Possibilité d'utilisation: Volant

Logistique

EAN / GTIN: 7640144991630

Poids: 2,35 kg

Longueur: 0.28 m

Largeur: 0.24 m

Hauteur: 0.13 m

- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

L'étendue des fournitures

- 1 x Laser, 1 x Mode d'emploi, 1 x Câble secteur/câble d'alimentation, 1 x Interlock, 1 x Clé

Données techniques:

| | |
|-----------------------------------|---|
| Alimentation électrique: | 100-240 V CA, 50/60 Hz |
| Puissance totale de raccordement: | 15 W |
| Type de protection: | IP20 |
| Branchement électrique: | Alimentation électrique via Appareils froids (M) câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite |
| Classe laser: | 3B |
| Couleur du laser: | R/G/B |
| Module laser: | Rouge (R) 70 mW 638nm Vert (G) 25 mW 532 nm B bleu 60 mW 450 nm |
| Commande: | DMX; stand-alone; commande de la musique via microphone |
| Couleur du boîtier: | Noir |
| Système d'enregistrement: | Étrier |
| Dimension: | Longueur : 0,205 cm Largeur : 0,145 cm Hauteur : 0,07 cm |
| Poids: | 1,92 kg |